

NODAL 50 L

Enriched Oil-based Form Release Agent

Description

Nodal 50 L is an enriched oil-based, ready-to-use form release agent which provides complete release of concrete or grout from metal or wooden formwork. It does not stain, extends the life of the formwork and provides a good quality aesthetic concrete finish.

Recommended Uses

- ✓ Mivan Shuttering Boards (Aluminium)
- ✓ MS Shuttering Boards
- ✓ Plywood Shuttering Boards
- ✓ FRP Boards

Advantages

- ✓ Provides quick, clean and easy stripping of moulds and formwork
- ✓ Offers very good surface finish to the concrete
- ✓ Easy release on all mould types
- ✓ Excellent mould releasing characteristics
- ✓ Non-toxic
- ✓ Extends the life of formwork
- ✓ Reduces surface blemishes
- ✓ Reduces remedial costs

Technical Properties

Appearance : Clear to Yellow liquid

Application Instructions

Mould Preparation

All moulds, new or used, must be cleaned of any kind of surface deposit before application. Inadequate cleaning may lead to surface blemishes due to the adhering material. Steel formwork must be dry. If forms are to be regularly re-used, then the surface should initially be coated with a suitable polyurethane sealer.

Application

Nodal 50 L can be applied by all normal methods, including brush, sponge, and conventional spray. Spray application is recommended wherever suitable. Ensure full mixing before applying.

Non-absorbent surfaces require a single application. New, unsealed, timber surfaces should be re-coated if delay in use of the mould leads to absorption of the release agent into the timber.

A preliminary trial must be carried out before full application in all situations. Overapplication should be avoided.

Cleaning of Equipment

Clean all tools and application equipment with cleaning solvent, dissolvent or petroleum ether immediately after use. Hardened material can only be removed mechanically.

Dosage

Dosage depends on the absorbency, surface porosity, roughness, surface profile, variations in level or wastage, etc. Actual consumption to be decided on site trials.

Coverage

Depending on the porosity and texture of the mould surface, typical coverage rates would be 10 m² to 15 m² per litre.

Storage

Nodal 50 L must be stored where temperature does not drop below 5°C, under cover, out of direct sunlight and to be protected from extremes of temperature.

Shelf life

12 months from the date of manufacture in unopened conditions.

Packaging

Nodal 50 L is available in 20 L buckets and 200 L HDPE barrels.

Safety

Before use, refer to the Material Safety Data Sheet (MSDS). The MSDS is available on www.ccichemicals.in or contact us at info@ccichemicals.in.

Registered Office	Regional Office	Chennai Plant	Mumbai Plant
Office No. 210 Shah Heritage Commercial CHS Plot No. 9, Sector 48, Seawood Navi Mumbai – 400 706 Maharashtra, India Mobile: +91 93247 27785 E-mail: kashinath.bera@ccichemicals.in	'LAKSHMAN MANERE' Old No. 17/2, New No. 42/2, R Block 6 th Main Road, Anna Nagar West Chennai – 600 040 Tamilnadu, India Mobile: +91 98400 73183 E-mail: durai.murugan@ccichemicals.in	No. 1, Perumal Koil Street Azhinjivakkam Sriperumpudhur Thiruvallur – 602 105 Tamilnadu, India	Plot No. A-51 Taloja Industrial Area MIDC, Taloja Navi Mumbai – 410 208 Maharashtra, India